HAZARDOUS AREA (EX) EQUIPMENT · APPLETON

APPLETON ECHF EXPLOSIONPROOF FLEXIBLE COUPLING

CODE ECHF ECHF



APPLETON ECHF

Standards: UL 844 and 886, CSA C22.2 No. 30

RANGE	Appleton ECHF · Hazardous area (Ex) equipment · 12 catalogue references
DIMENSION A	85.85 mm
DIMENSION B	47.75 mm
PROTECTION	Explosionproof, dust-ignitionproof
HAZARDOUS LOCATIONS	Class I, Div 1 & 2, Groups A, B, C, D; Class I, Zone 1 & 2, Groups IIA, IIB, IIC; Class II, Div 1 & 2, Groups E, F, G; Class III
MATERIAL	Brass tubing, bronze outer braid, insulating liner; bronze female end fittings
ENDS	Female, with two removable steel close nipples
REFERENCES	• ECHF-50-4 · 1/2", 4" (101.60 mm) flexible length • ECHF-50-6 · 1/2", 6" (152.40 mm) flexible length • ECHF-50-8 · 1/2", 8" (203.20 mm) flexible length • ECHF-50-10 · 1/2", 10" (254.00 mm) flexible length • ECHF-50-12 · 1/2", 12" (304.80 mm) flexible length • ECHF-50-15 · 1/2", 15" (381.00 mm) flexible length • ECHF-50-18 · 1/2", 18" (457.20 mm) flexible length • ECHF-75-4 · 3/4", 4" (101.60 mm) flexible length • ECHF-75-6 · 3/4", 6" (152.40 mm) flexible length • + 3 more references on sixwinds.com.sa (search "Appleton ECHF")