HAZARDOUS AREA (EX) EQUIPMENT · APPLETON

APPLETON OE EXPLOSIONPROOF CONDUIT OUTLET BOX

CODE OE OE

Standards: UL 886, UL Listed E85310, CSA C22.2



APPLETON OE

RANGE	Appleton OE · Hazardous area (Ex) equipment · 10 catalogue references
PROTECTION	Explosionproof, dust-ignitionproof
HAZARDOUS LOCATIONS	Class I, Div 1 & 2, Groups C, D; Class II, Div 1 & 2, Groups E, F, G; Class III
MATERIAL	Malleable iron body and cover
FINISH	Triple coat: zinc electroplate, chromate, epoxy powder coat
CONDUIT	Threaded rigid metal conduit
SUPPLIED WITH	Blank cover
REFERENCES	• 0EC-50 · type C, 1/2" hubs, malleable iron • 0EC-75 · type C, 3/4" hubs, malleable iron • 0ELB-50 · type LB, 1/2" hubs, malleable iron • 0ELB-75 · type LB, 3/4" hubs, malleable iron • 0ELL-50 · type LL, 1/2" hubs, malleable iron • 0ELL-75 · type LL, 3/4" hubs, malleable iron • 0ELR-50 · type LR, 1/2" hubs, malleable iron • 0ELR-75 · type LR, 3/4" hubs, malleable iron • 0ET-50 · type T, 1/2" hubs, malleable iron • + 1 more references on sixwinds.com.sa (search "Appleton OE")