CABLE ACCESSORIES · ELASTIMOLD

ELASTIMOLD RANGER2 TERMINATIONS

CODE RANGER2 (R2T | **RANGER2 (R2T**

Ambient temperature: -30 °C to 65 °C



ELASTIMOLD RANGER2 (R2T

RANGE	Elastimold Ranger2 (R2T · Cable accessories · 30 catalogue references
STANDARD	IEEE 48
AMBIENT TEMPERATURE	-30 °C to 65 °C
FREQUENCY	48 to 62 Hz
ALTITUDE	3,300 ft max.
CABLE	XLPE and EPR, #2 AWG to 1250 kcmil
MOUNTING	Free hanging or optional bracket
REFERENCES	• R2IT15J1 · indoor termination, 15 kV, insulation 16.3 to 28.4 mm • R2IT15M1 · indoor termination, 15 kV, insulation 16.3 to 28.4 mm • R2IT15L1 · indoor termination, 15 kV, insulation 16.3 to 28.4 mm • R2IT15J2 · indoor termination, 15 kV, insulation 21.3 to 35.1 mm • R2IT15M2 · indoor termination, 15 kV, insulation 21.3 to 35.1 mm • R2IT15L2 · indoor termination, 15 kV, insulation 21.3 to 35.1 mm • R2IT15J4 · indoor termination, 15 kV, insulation 33.0 to 53.3 mm • R2IT15M4 · indoor termination, 15 kV, insulation 33.0 to 53.3 mm • R2IT15L4 · indoor termination, 15 kV, insulation 33.0 to 53.3 mm • + 21 more references on sixwinds.com.sa (search "Elastimold Ranger2")