CENTRIFUGAL FANS · DC MOTOR

KRUBO DC BACKWARD-CURVED CENTRIFUGAL FANS

CODES SWK-DC250-R48-30 – SWK-DC310-R48-17 | **BRAND: KRUBO** | **14 MODELS**



- 250 – 310 MM
- 24 V · 48 V · 26 V
- IP44
- SPEED CONTROL 1-10 V/PWM
- MAINTENANCE FREE BALL BEARINGS
- INSULATION B

DESCRIPTION

Krubo DC backward-curved centrifugal fans, listed by Six Winds code and Krubo model. Search either code on sixwinds.com.sa for the full specification of each model.

SIX WINDS CODE	KRUBO MODEL	SIZE	VOLTAGE	POWER	SPEED	AIRFLOW
SWK-DC250-R48-30	K-DC250-R48-30	250 mm	48 V	228 W		1900 m³/h
SWK-DC280-R24-19	K-DC280-R24-19	280 mm	24 V	139 W	1940 rpm	2185 m³/h
SWK-DC280-R24-24	K-DC280-R24-24	280 mm				
SWK-DC280-R26-28	K-DC280-R26-28	280 mm	26 V	468 W	2800 rpm	
SWK-DC280-R48-17	K-DC280-R48-17	280 mm	48 V	86 W	1700 rpm	1960m³/h
SWK-DC280-R48-19	K-DC280-R48-19	280 mm				
SWK-DC280-R48-24	K-DC280-R48-24	280 mm				
SWK-DC280-R80-28	K-DC280-R80-28	280 mm	80VDC	385 W±10%	2820 rpm±10%	2820 m³/h
SWK-DC310-R150-26H	K-DC310-R150-26H	310 mm	150 V		2660 rpm	
SWK-DC310-R24-16	K-DC310-R24-16	310 mm	24 V		1600 rpm	2175m³/h
SWK-DC310-R24-19	K-DC310-R24-19	310 mm	24 V	208 W		2620m³/h
SWK-DC310-R24-20	K-DC310-R24-20	310 mm	24 V	202 W		2200m³/h
SWK-DC310-R48-16	K-DC310-R48-16	310 mm				
SWK-DC310-R48-17	K-DC310-R48-17	310 mm				

Values as stated by the manufacturer; "/" separates 50 Hz / 60 Hz or speed steps. Other voltages and versions on request.