COMPACT FANS · EC

KRUBO EC COMPACT COOLING FANS

CODES SWK-EC8025 – SWK-E20053-A220-38 | **BRAND: KRUBO** | **12 MODELS**



- 80 – 200 MM
- 110 V / 220 V · 220 V · 110 V/220 V
- BALL BEARING
- INSULATION CLASS F
- ROHS, UR, ISO, CE, CCC

DESCRIPTION

Krubo EC compact cooling fans, listed by Six Winds code and Krubo model. Search either code on sixwinds.com.sa for the full specification of each model.

SIX WINDS CODE	KRUBO MODEL	SIZE	VOLTAGE	POWER	SPEED	AIRFLOW
SWK-EC8025	K-EC8025	80 × 80 × 25 mm	110 V / 220 V	2.8~4 W	3000~4500 rpm	32.23~48.82 CFM
SWK-EC8038	K-EC8038	80 × 80 × 38 mm	110 V / 220 V	4.5~6.5 W	3500~4500 rpm	48.5~62.3 CFM
SWK-EC8038-A220-45	K-EC8038-A220-45	80 × 80 × 38 mm	110 V/220 V	4 W	4500 rpm	48.82 CFM
SWK-EC092-Q230-25	K-EC092-Q230-25	92 mm				
SWK-EC9225	K-EC9225	92 × 92 × 25 mm	110 V / 220 V	3~6 W	2500~3500 rpm	53.63~75.09 CFM
SWK-EC9238	K-EC9238	92 × 92 × 38 mm	110 V / 220 V	4.5~6.5 W	3000~4200 rpm	75.73~106.02 CFM
SWK-EC120	K-EC120	120 mm	110 V / 220 V	2.3~9 W	2000~4000 rpm	77.53~185.53 CFM
SWK-EC12038-A220-30	K-EC12038-A220-30	120 × 120 × 38 mm	190~250 V	5 W	3000 rpm	110.92 CFM
SWK-EC12038-A220-40	K-EC12038-A220-40	120 × 120 × 38 mm	220 V	9 W	4000 rpm	185.53 CFM
SWK-EC12038-A220-41H	K-EC12038-A220-41H	120 × 120 × 38 mm	220 V AC			
SWK-EC17251	K-EC17251	172 × 150 × 51 mm	110 V / 220 V	14~60 W	3000~5000 rpm	225~363 CFM
SWK-E20053-A220-38	K-E20053-A220-38	200 × 200 × 53 mm	220 V		3800 rpm±10%	

Values as stated by the manufacturer; "/" separates 50 Hz / 60 Hz or speed steps. Other voltages and versions on request.