MINING · BLASTING · ANTI-STATIC LOADING HOSE

ANFO EXPLOSIVE LOADING HOSE

CODE ANFO | **IN STOCK IN JEDDAH** | **ANTI-STATIC**



ANTI-STATIC · ORANGE STRIPE

- Static-dissipating
- Stray-current resistant
- Self-extinguishing
- Orange visibility stripe
- -35 to +65 °C



Smooth bore, striped cover

DESCRIPTION	Anti-static (conductive) hose for pneumatic loading of ANFO blasting agents into blast holes
APPLICATIONS	• Open-pit and underground mining • Quarrying and tunnelling • Construction blasting
MATERIAL	Anti-static thermoplastic compound
STATIC CONTROL	Drains static charge from pneumatic loading to ground through the loader
STRAY CURRENT	Resistance set to guard the blasting circuit against stray currents
FIRE BEHAVIOUR	Self-extinguishing
IDENTIFICATION	Continuous orange stripe for visibility underground
TEMPERATURE	-35 °C to +65 °C
SIZES (ID × OD, COIL)	• 5/8 in (16 mm) × 22 mm OD, 61 m coil • 3/4 in (19 mm) × 27 mm OD, 61 m coil • 1 in (25 mm) × 34 mm OD, 91 m coil • 1-1/4 in (32 mm) × 41 mm OD, 30 m coil
WEIGHT PER 100 M	Approx. 25, 40, 55 and 78 kg (by size, smallest first)
MAX. WORKING PRESSURE	120 psi (0.83 MPa)
BURST PRESSURE	Confirmed with the quotation

SIX WINDS TRADING
Industrial & electrical supply · Jeddah, Saudi Arabia · CR 4030400579
Price, stock and delivery on request · specifications as stated by the manufacturer

Tel +966 12 661 5115
sales@sixwinds.com.sa · sixwinds.com.sa