HAZARDOUS AREA (EX) EQUIPMENT · MARECHAL ELECTRIC

MARECHAL B2X EX INCREASED-SAFETY JUNCTION BOXES

CODE B2X INCREASED-SAFETY ENCLOSURES | **IP66 / IP67** | **GRP (POLYESTER)**



MARECHAL B2X INCREASED-SAFETY ENCLOSURES

- **Ex marking: II 2 G Ex e IIC Gb, or Ex ia / ib**
- **Zones: 1, 2, 21, 22**
- **Impact: IK09**
- **Standards: IEC/EN 60079-0, 60079-7, 60079-11,**
- **Operating temperature: -50 °C to +60 °C**

RANGE	B2X increased-safety enclosures · Hazardous area (Ex) equipment · 40 catalogue references
EX MARKING	II 2 G Ex e IIC Gb, or Ex ia / ib IIC Gb, or Ex e ia / ib IIC Gb; II 2 D Ex tb IIIC Db
CERTIFICATES	IECEx LCIE 16.0042X; LCIE 16 ATEX 3054X
ZONES	1, 2, 21, 22
BODY	GRP (polyester)
DEGREE OF PROTECTION	IP66 / IP67
IMPACT	IK09
REFERENCES	• 209AC12 · Empty enclosure • 209AC16 · Empty enclosure • 209ACP12 · Empty enclosure • 209ACP16 · Empty enclosure • 24A1C0000J169 · Configured Ex e junction box for non-armoured cable • 24A1C0000J170 · Configured Ex e junction box for non-armoured cable • 24A1C0000J171 · Configured Ex e junction box for non-armoured cable • 24A1D0000J172 · Configured Ex e junction box for non-armoured cable • 24A1D0000J173 · Configured Ex e junction box for non-armoured cable • + 31 more references on sixwinds.com.sa (search "Marechal B2X")