INDUSTRIAL PLUGS AND SOCKETS · MARECHAL ELECTRIC

MARECHAL DS1 DECONTACTOR SWITCH-RATED PLUGS AND SOCKETS

CODE DS1 DECONTACTOR | **30 A** | **IP54 (PLUG CONNECT** | **GRP (POLYESTER)**



MARECHAL DS1 DECONTACTOR

Impact: IK09

Operating temperature: -40 °C to +60 °C

Utilisation category: AC-22A / AC-23A / DC-21A

RANGE	DS1 DECONTACTOR · Industrial plugs and sockets · 12 catalogue references
RATED CURRENT	30 A
RANGE MAX. VOLTAGE	690 V AC / 1000 V DC
BODY	GRP (polyester)
DEGREE OF PROTECTION	IP54 (plug connected) / IP55 (lid closed)
IMPACT	IK09
CABLE SIZE	2.5-6 mm² flexible, 2.5-10 mm² stranded
REFERENCES	• 311408A · Socket-outlet · 2P · 20-24 V AC • 311808A · Inlet · 2P · 20-24 V AC • 3114015 · Socket-outlet · 1P+N+E · 190-250 V AC • 3118015 · Inlet · 1P+N+E · 190-250 V AC • 3114013 · Socket-outlet · 3P+E · 380-440 V AC • 3118013 · Inlet · 3P+E · 380-440 V AC • 3114017 · Socket-outlet · 3P+N+E · 190-250/380-440 V AC • 3118017 · Inlet · 3P+N+E · 190-250/380-440 V AC • 3114193 · Socket-outlet · 3P+E · 660-690 V AC • + 3 more references on sixwinds.com.sa (search "Marechal DS1")