INDUSTRIAL PLUGS AND SOCKETS · MARECHAL ELECTRIC

MARECHAL DS2 DECONTACTOR SWITCH-RATED PLUGS AND SOCKETS

CODE DS2 DECONTACTOR | **250 A** | **IP66 / IP67** | **METAL**



MARECHAL DS2 DECONTACTOR

- **Impact: IK10**
- **Operating temperature: -40 °C to +60 °C**
- **Utilisation category: AC-22A / AC-23A / DC-21A**
- **Standards: IEC/EN 60309-1, IEC/EN 60309-4, IEC**

RANGE	DS2 DECONTACTOR · Industrial plugs and sockets · 10 catalogue references
RATED CURRENT	250 A
MAXIMUM VOLTAGE	1000 V AC / 1500 V DC
BODY	Metal
DEGREE OF PROTECTION	IP66 / IP67
IMPACT	IK10
CABLE SIZE	70-95 mm² flexible, 70-120 mm² stranded (larger with amplifier lugs 392A277150 / 392A277185)
REFERENCES	• 3924013 · Socket-outlet · 3P+E · 380-440 V AC • 3928013 · Inlet · 3P+E · 380-440 V AC • 3924017 · Socket-outlet · 3P+N+E · 190-250 V AC / 380-440 V AC • 3928017 · Inlet · 3P+N+E · 190-250 V AC / 380-440 V AC • 3924193 · Socket-outlet · 3P+E · 660-690 V AC • 3928193 · Inlet · 3P+E · 660-690 V AC • 3924197 · Socket-outlet · 3P+N+E · 660-690 V AC • 3928197 · Inlet · 3P+N+E · 660-690 V AC • 3924223 · Socket-outlet · 3P+E · 1000 V AC • + 1 more references on sixwinds.com.sa (search "Marechal DS2")