INDUSTRIAL PLUGS AND SOCKETS · MARECHAL ELECTRIC

MARECHAL DS3 DECONTACTOR SWITCH-RATED PLUGS AND SOCKETS

CODE DS3 DECONTACTOR | **50 A** | **IP54 (PLUG CONNECT** | **GRP (POLYESTER)**



MARECHAL DS3 DECONTACTOR

Impact: IK09

Operating temperature: -40 °C to +60 °C

Utilisation category: AC-22A / AC-23A / DC-21A

RANGE	DS3 DECONTACTOR · Industrial plugs and sockets · 14 catalogue references
RATED CURRENT	50 A
RANGE MAX. VOLTAGE	1000 V AC / 1500 V DC
BODY	GRP (polyester)
DEGREE OF PROTECTION	IP54 (plug connected) / IP55 (lid closed)
IMPACT	IK09
CABLE SIZE	6-16 mm² flexible, 10-25 mm² stranded
REFERENCES	• 313408A · Socket-outlet · 2P · 20-24 V AC • 313808A · Inlet · 2P · 20-24 V AC • 3134015 · Socket-outlet · 1P+N+E · 190-250 V AC • 3138015 · Inlet · 1P+N+E · 190-250 V AC • 3134013 · Socket-outlet · 3P+E · 380-440 V AC • 3138013 · Inlet · 3P+E · 380-440 V AC • 3134017 · Socket-outlet · 3P+N+E · 190-250/380-440 V AC • 3138017 · Inlet · 3P+N+E · 190-250/380-440 V AC • 3134193 · Socket-outlet · 3P+E · 660-690 V AC • + 5 more references on sixwinds.com.sa (search "Marechal DS3")