INDUSTRIAL PLUGS AND SOCKETS · MARECHAL ELECTRIC

MARECHAL DS6 DECONTACTOR SWITCH-RATED PLUGS AND SOCKETS

CODE DS6 DECONTACTOR | **90 A** | **IP66/IP67**



MARECHAL DS6 DECONTACTOR

- **Operating temperature: -40 °C to +60 °C**
- **Utilisation category: AC-22A / AC-23A / DC-21A**
- **Standards: IEC/EN 60309-1, IEC/EN 60309-4, IEC**

RANGE	DS6 DECONTACTOR · Industrial plugs and sockets · 24 catalogue references
RATED CURRENT	90 A
RANGE MAX. VOLTAGE	1000 V AC / 1500 V DC
DEGREE OF PROTECTION	IP66/IP67
CABLE SIZE	10-25 mm² flexible, 10-35 mm² stranded
OPERATING TEMPERATURE	-40 °C to +60 °C
UTILISATION CATEGORY	AC-22A / AC-23A / DC-21A
REFERENCES	• 3164015 · Socket-outlet · 1P+N+E · 190-250 V AC • 3168015 · Inlet · 1P+N+E · 190-250 V AC • 3164013 · Socket-outlet · 3P+E · 380-440 V AC • 3168013 · Inlet · 3P+E · 380-440 V AC • 3164017 · Socket-outlet · 3P+N+E · 190-250/380-440 V AC • 3168017 · Inlet · 3P+N+E · 190-250/380-440 V AC • 3164193 · Socket-outlet · 3P+E · 660-690 V AC • 3168193 · Inlet · 3P+E · 660-690 V AC • 3164197 · Socket-outlet · 3P+N+E · 660-690 V AC • + 15 more references on sixwinds.com.sa (search "Marechal DS6")