INDUSTRIAL PLUGS AND SOCKETS · MARECHAL ELECTRIC

MARECHAL DS7C3 DECONTACTOR SWITCH-RATED PLUGS AND SOCKETS

CODE DS7C3 DECONTACTOR | **50 A** | **IP66/IP67**



MARECHAL DS7C3 DECONTACTOR

- **Impact: IK09**
- **Operating temperature: -40 °C to +60 °C**
- **Utilisation category: AC-22A / DC-21A**
- **Standards: IEC/EN 60309-1, IEC/EN 60309-4, IEC**

RANGE	DS7C3 DECONTACTOR · Industrial plugs and sockets · 8 catalogue references
RATED CURRENT	50 A
RANGE MAX. VOLTAGE	500 V AC / 750 V DC
DEGREE OF PROTECTION	IP66/IP67
IMPACT	IK09
CABLE SIZE	2.5-6 mm² flexible, 2.5-10 mm² stranded (screw terminals, 2.5-10 mm²)
OPERATING TEMPERATURE	-40 °C to +60 °C
REFERENCES	• 3134561 · Socket-outlet · 6P+E · max 500 V AC • 3138561 · Inlet · 6P+E · max 500 V AC • 3134561972 · Socket-outlet · 6P+E+3 aux. · max 500 V AC • 3138561972 · Inlet · 6P+E+3 aux. · max 500 V AC • 3934561 · Socket-outlet · 6P+E · max 500 V AC • 3938561 · Inlet · 6P+E · max 500 V AC • 3934561972 · Socket-outlet · 6P+E+3 aux. · max 500 V AC • 3938561972 · Inlet · 6P+E+3 aux. · max 500 V AC