HAZARDOUS AREA (EX) EQUIPMENT · MARECHAL ELECTRIC

MARECHAL DX6 EX DECONTACTOR SWITCH-RATED PLUGS AND SOCKETS

CODE DX6 DECONTACTOR (METAL) | **63 A** | **METAL**



MARECHAL DX6 DECONTACTOR (METAL)

- **Ex marking: II 2 G D Ex de IIC tD A21**
- **Zones: 1, 2, 21, 22**
- **Temperature class: T5 / T90 °C at -40 °C to +6**
- **Ambient temperature: -40 °C to +60 °C**

RANGE	DX6 DECONTACTOR (metal) · Hazardous area (Ex) equipment · 9 catalogue references
RATED CURRENT	63 A
MAX. VOLTAGE	750 V AC / 750 V DC
EX MARKING	II 2 G D Ex de IIC tD A21
CERTIFICATES	IECEx LCI 09.0015 / LCIE 04 ATEX 6038
ZONES	1, 2, 21, 22
GAS GROUP	IIC
REFERENCES	• 2664015 · Socket-outlet · 1P+N+E · 190-250 V AC • 2666015 · Inclined appliance inlet · 1P+N+E · 190-250 V AC • 2661015 · Plug · 1P+N+E · 190-250 V AC • 2664013 · Socket-outlet · 3P+E · 380-440 V AC • 2666013 · Inclined appliance inlet · 3P+E · 380-440 V AC • 2661013 · Plug · 3P+E · 380-440 V AC • 2664017 · Socket-outlet · 3P+N+E · 380-440 V AC • 2666017 · Inclined appliance inlet · 3P+N+E · 380-440 V AC • 2661017 · Plug · 3P+N+E · 380-440 V AC