HAZARDOUS AREA (EX) EQUIPMENT · MARECHAL ELECTRIC

MARECHAL DXN1 EX DECONTACTOR SWITCH-RATED PLUGS AND SOCKETS

CODE DXN1 DECONTACTOR (ZONE 1/21) | **20 A** | **GRP**



MARECHAL DXN1 DECONTACTOR (ZONE 1/21)

- **Ex marking: II 2 G D Ex db eb IIC T6 or T5 Gb**
- **Zones: 1, 2, 21, 22**
- **Temperature class: T6 at -40 °C to +40 °C, T5**
- **Ambient temperature: -40 °C to +60 °C**

RANGE	DXN1 DECONTACTOR (Zone 1/21) · Hazardous area (Ex) equipment · 20 catalogue references
RATED CURRENT	20 A
MAX. VOLTAGE	550 V AC / 550 V DC
EX MARKING	II 2 G D Ex db eb IIC T6 or T5 Gb / Ex tb IIIC T70 °C or T90 °C Db
CERTIFICATES	IECEx LCI 09.0005X / LCIE 99 ATEX 6027 X
ZONES	1, 2, 21, 22
GAS GROUP	IIC
REFERENCES	• 251408A · Socket-outlet · 2P · 20-24 V AC • 251808A · Inlet · 2P · 20-24 V AC • 2514015 · Socket-outlet · 1P+N+E · 190-250 V AC • 2518015 · Inlet · 1P+N+E · 190-250 V AC • 2514013 · Socket-outlet · 3P+E · 380-440 V AC • 2518013 · Inlet · 3P+E · 380-440 V AC • 2514017 · Socket-outlet · 3P+N+E · 380-440 V AC • 2518017 · Inlet · 3P+N+E · 380-440 V AC • 2514093 · Socket-outlet · 3P+E · 480-500 V AC • + 11 more references on sixwinds.com.sa (search "Marechal DXN1")