HAZARDOUS AREA (EX) EQUIPMENT · MARECHAL ELECTRIC

MARECHAL DXN25C EX MULTICONTACT CONNECTORS

CODE DXN25C | **10 A (4-20 MA SIGN**



MARECHAL DXN25C

- **Ex marking: II 2 G D Ex e IIC T6 or T5 Gb / Ex**
- **Zones: 1, 2, 21, 22**
- **Temperature class: T6 / T51 °C at -40 °C to +4**
- **Ambient temperature: -40 °C to +60 °C**

RANGE	DXN25C · Hazardous area (Ex) equipment · 10 catalogue references
CONTACTS	25 (24+E)
RATED CURRENT	10 A (4-20 mA signals to 10 A)
MAX. VOLTAGE	440 V AC / 440 V DC
EX MARKING	II 2 G D Ex e IIC T6 or T5 Gb / Ex tb IIIC T51 °C or T71 °C Db (or Ex ia/ib IIC T6 Gb)
CERTIFICATES	IECEx LCIE 14.0040X / LCIE 09 ATEX 3050X
ZONES	1, 2, 21, 22
REFERENCES	• 36D000232M · Wall-mounting socket-outlet • 36D0002 · Wall-mounting socket-outlet • 36D100232M · Plug • 36D1002 · Plug • 36D7002 · Inclined socket-outlet • 36D9002 · Inclined appliance inlet • 36D300232M · Coupler socket / in-line connector • 36D3002 · Coupler socket / in-line connector • 36D600232M · Wall-mounting appliance inlet • + 1 more references on sixwinds.com.sa (search "Marechal DXN25C")