HAZARDOUS AREA (EX) EQUIPMENT · MARECHAL ELECTRIC

MARECHAL DXN37C EX MULTICONTACT CONNECTORS

CODE DXN37C | **10 A (4-20 MA SIGN**



MARECHAL DXN37C

- **Ex marking: II 2 G D Ex eb IIC T6 or T5 Gb / E**
- **Zones: 1, 2, 21, 22**
- **Temperature class: T6 / T56 °C at -40 °C to +4**
- **Ambient temperature: -40 °C to +55 °C**

RANGE	DXN37C · Hazardous area (Ex) equipment · 10 catalogue references
CONTACTS	37 (36+E)
RATED CURRENT	10 A (4-20 mA signals to 10 A)
MAX. VOLTAGE	230 V AC / 230 V DC
EX MARKING	II 2 G D Ex eb IIC T6 or T5 Gb / Ex tb IIIC T56 °C or T76 °C Db (or Ex ia/ib IIC T6 Gb)
CERTIFICATES	IECEx LCIE 14.0038X / LCIE 07 ATEX 6071X
ZONES	1, 2, 21, 22
REFERENCES	• 36C000332M · Wall-mounting socket-outlet • 36C0003 · Wall-mounting socket-outlet • 36C100332M · Plug • 36C1003 · Plug • 36C7003 · Inclined socket-outlet • 36C9003 · Inclined appliance inlet • 36C300332M · Coupler socket / in-line connector • 36C3003 · Coupler socket / in-line connector • 36C600332M · Wall-mounting appliance inlet • + 1 more references on sixwinds.com.sa (search "Marechal DXN37C")