INDUSTRIAL PLUGS AND SOCKETS · MARECHAL ELECTRIC

MARECHAL EVO40 SEPARABLE SWITCH-DISCONNECTOR

CODE EVO40 SEPARABLE SWITCH-DISCONNECTOR | **40 A (ITHE)** | **IP66/IP67/IP69; IP** | **GLASS-REINFORCED P**

Impact: IK09



MARECHAL EVO40 SEPARABLE SWITCH-DISCONNECTOR

RANGE	EVO40 separable switch-disconnector · Industrial plugs and sockets · 24 catalogue references
RATED CURRENT	40 A (Ithe)
MAX OPERATIONAL VOLTAGE	690 V AC / 250 V DC
SWITCHING CAPACITY	AC-21A/AC-22A 40 A at 230/400/690 V; AC-23A 11 kW (230 V), 18.5 kW (400/690 V); AC-3 7.5 kW (230 V), 11 kW (400/690 V); DC-21A 8 kW (250 V)
RATED INSULATION VOLTAGE	1000 V AC
RATED IMPULSE WITHSTAND VOLTAGE	8 kV
ELECTRICAL ENDURANCE	15 000 cycles (AC-23A, 690 V AC / 40 A)
REFERENCES	• 8144032 · 2P+E · 190-250 V AC • 8148032 · 2P+E · 190-250 V AC • 8144033 · 3P+E · 190-250 V AC • 8148033 · 3P+E · 190-250 V AC • 8144034 · 4P+E · 190-250 V AC • 8148034 · 4P+E · 190-250 V AC • 814403W · 6P+E · 190-250 V AC • 814803W · 6P+E · 190-250 V AC • 8144012 · 2P+E · 380-440 V AC • + 15 more references on sixwinds.com.sa (search "Marechal EVO40")