HAZARDOUS AREA (EX) EQUIPMENT · MARECHAL ELECTRIC

MARECHAL PXN12C EX MULTICONTACT CONNECTORS

CODE PXN12C | **10 A (4-20 MA SIGN**



MARECHAL PXN12C

- **Ex marking: II 2 G D Ex e IIC T5 Gb / Ex tb II**
- **Zones: 1, 2, 21, 22**
- **Temperature class: T5 (Ex e) or T6 (Ex ia/ib);**
- **Ambient temperature: -40 °C to +55 °C**

RANGE	PXN12C · Hazardous area (Ex) equipment · 10 catalogue references
CONTACTS	12 (11+E)
RATED CURRENT	10 A (4-20 mA signals to 10 A)
MAX. VOLTAGE	220 V AC / 220 V DC
EX MARKING	II 2 G D Ex e IIC T5 Gb / Ex tb IIIC T69 °C Db (or Ex ia/ib IIC T6 Gb / Ex tb IIIC T69 °C Db)
CERTIFICATES	IECEx LCIE 14.0041X / LCIE 07 ATEX 6070X
ZONES	1, 2, 21, 22
REFERENCES	• 06A000125M · Wall-mounting socket-outlet • 06A0001 · Wall-mounting socket-outlet • 06A100125M · Plug • 06A1001 · Plug • 06A7001 · Inclined socket-outlet • 06A9001 · Inclined appliance inlet • 06A300125M · Coupler socket / in-line connector • 06A3001 · Coupler socket / in-line connector • 06A600125M · Wall-mounting appliance inlet • + 1 more references on sixwinds.com.sa (search "Marechal PXN12C")