INDUSTRIAL PLUGS AND SOCKETS · MARECHAL ELECTRIC

MARECHAL SP SINGLE-POLE CONNECTORS

CODE SP | **800 A** | **IP66 / IP67 (WHEN** | **GRP**



MARECHAL SP

Impact: IK08

Operating temperature: -40 °C to +60 °C

RANGE	SP · Industrial plugs and sockets · 42 catalogue references
RATED CURRENT	800 A
MAXIMUM VOLTAGE	1000 V AC / 1500 V DC
BODY	GRP
IMPACT	IK08
DEGREE OF PROTECTION	IP66 / IP67 (when connected); IP2X with cap removed
CABLE SIZE	70-630 mm² via copper lugs (see lug table)
REFERENCES	• 4544001 · Socket-outlet · 1000 V AC / 1500 V DC • 4548001 · Inlet · 1000 V AC / 1500 V DC • 4544002 · Socket-outlet · 1000 V AC / 1500 V DC • 4548002 · Inlet · 1000 V AC / 1500 V DC • 4544003 · Socket-outlet · 1000 V AC / 1500 V DC • 4548003 · Inlet · 1000 V AC / 1500 V DC • 454400N · Socket-outlet · 1000 V AC / 1500 V DC • 454800N · Inlet · 1000 V AC / 1500 V DC • 454400T · Socket-outlet · 1000 V AC / 1500 V DC • + 33 more references on sixwinds.com.sa (search "Marechal SP")