HAZARDOUS AREA (EX) EQUIPMENT · MARECHAL ELECTRIC

MARECHAL SPEX EX SINGLE-POLE CONNECTORS

CODE SPEX | UP TO 680 A (DEPEN | GRP



MARECHAL SPEX

- Ex marking: II 2 G D Ex e IIC Gb / Ex tb IIIC
- Zones: 1, 2, 21, 22
- Temperature class: T5 / T56 °C or T6 / T56 °C
- Ambient temperature: -20 °C to +60 °C

RANGE	SPeX · Hazardous area (Ex) equipment · 105 catalogue references
RATED CURRENT	Up to 680 A (depends on temperature class and cable size)
MAX. VOLTAGE	1000 V AC / 1000 V DC
EX MARKING	II 2 G D Ex e IIC Gb / Ex tb IIIC Db
CERTIFICATES	IECEx LCI 12.0005X / LCIE 07 ATEX 6073 X
ZONES	1, 2, 21, 22
GAS GROUP	IIC
REFERENCES	• 4647001 · Inclined socket-outlet · 1 pole + pilot • 464100132P · Plug · 1 pole + pilot • 464100140P · Plug · 1 pole + pilot • 464100150P · Plug · 1 pole + pilot • 464100163P · Plug · 1 pole + pilot • 4647002 · Inclined socket-outlet · 1 pole + pilot • 464100232P · Plug · 1 pole + pilot • 464100240P · Plug · 1 pole + pilot • 464100250P · Plug · 1 pole + pilot • + 96 more references on sixwinds.com.sa (search "Marechal SPeX")